



NOTE:

1. FOR USE OVER INSULATION, POURED CONCRETE AND OTHER PROPERLY PREPARED ACCEPTABLE NON-NAILABLE ROOF DECKS.
2. DO NOT APPLY RUBEROID TORCH OR RUBEROID HEATWELD MEMBRANES DIRECTLY TO STRATVENT PERFORATED VENTING BASE SHEET. AT LEAST ONE PLY OF GAFGLAS #75 BASE SHEET OR 2 PLIES OF GAFGLAS PLY SHEETS MUST BE HOT MOPPED OVER STRATVENT PERFORATED VENTING BASE SHEET BEFORE TORCH APPLYING RUBEROID MEMBRANES.
3. REFER TO MB/BUR SYSTEMS INSTALLATION REQUIREMENT SECTION.
4. WHEN THE MINIMUM DIMENSION OF THE ROOF EXCEEDS 60 FEET, TOP SIDE FIELD VENTING SHOULD BE USED IN ADDITION OF THE EDGE AND PARAPET WALL VENTING. ROOF VENTS ARE TO BE APPLIED AT THE RATE OF ONE VENT PER 1,000 SQUARE FT. OF ROOF AREA.



GAFGLAS®
Built-Up Roofing Systems
RUBEROID®
Modified Bitumen Roofing Systems

**STRATAVENT® ELIMINATOR™ PERFORATED
VENTING DETAIL, NEW ROOFING -
NON-NAILABLE DECK**

DRAWING #

35

SYSTEM

MB/BUR

SCALE

N.T.S.

ISSUE/REVISION DATE

5-01-09